

## Descriptions

This is a USB to RS-422/RS-485 serial port converter which uses the FTDI chipset. Can support with RS-422 / RS-485 interface equipment: surveillance cameras, video collector, fingerprint attendance machine, program-controlled switches, numerical control machine, microcontroller, etc

Support for Win7/Win8/Win10 and the most common operating systems Linux (2.4 and above) / Mac OS (8.9 and above).



## Specification

Add an RS-485/RS-422 Port to your PC with USB connection

Standard: USB 2.0, backwards compatible with USB 1.1

Compliant to: RS-422 RS-485 standard

Direction control: Using data flow to the automatic control technology, automatic discrimination and control data transmission direction

Baud rate: 300-9216000 BPS, automatic detection serial signal rate

Load capacity: support point to more, each machine converter allows connection 32 RS-422 or RS-485 interface equipment

Interface protection: surge protection power 600 W,  $\pm 15$  kV electrostatic protection

support Windows 10 (32/64) / Windows 8 (32/64) / Windows 7 (32/64) / Vista (32/64) / XP (32/64)

## Highlights

Tough rubberized plastic overmolded construction.

Our most compact form factor.

Powerful USB Line Drivers

No external power supply, plug-and-play.

Automatic baud rate detection.

Uses data flow control technology which automatically controls the TX enable data direction on the bus.